

KINGLIFT

MINI SCISSOR LIFTS SERIES



 HIGHLIGHTS

High Performance

- ▶ Fault codes are automatically displayed for easy maintenance
- ▶ The foldable fence reduces the volume of the whole machine
- ▶ Convenient for working in tight spaces
- ▶ 25% climbing ability, able to smoothly climb up the slope
- ▶ Swivel chassis for easy maintenance
- ▶ The pedal extension platform can be quickly rolled out to the operating point

 FEATURES

Safety Configuration

- Automatic braking system

Emergency descent system

Charging protection system

Oil pipe explosion-proof system

Tilt protection system

Automatic pothole protection

Emergency stop button

Tamper-proof
- Platform self-locking door

Foldable fence

Other Configuration

- Full Self-propelled
- Non-marking tire
- 4×2 drive
- Extended platform
- Horn& Buzzer
- Standard transport forklift hole
- Work schedule
- Continuously variable speed



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT MINI SCISSOR LIFT SERIES

Model	GTJZD04	QY0508DEM	GTJZ0607HD	GTJZ0608HD	GTJZ0612HD
Size					
Working Height	6m	6.5m	7.8m	7.80m	7.80m
A-Platform Height-Elevated	4m	4.5m	5.8m	5.80m	5.80m
B-Platform height-Stowed	0.95m	0.99m	1.1m	1.1m	1.1m
C-Platform Length	1.29m	1.29m	1.67m	2.26	2.29m
D-Platform Width	0.7m	0.7m	0.74m	0.81m	1.15m
Platform Extension	0.6m	0.6m	0.9m	0.9m	0.9m
E-Overall Height (unfolded guardrail)	2.00m	2.09m	2.21m	2.2m	2.2m
Overall height (folded guardrail)	1.63m	1.73m	1.85m	1.73m	1.68m
F-Overall Length	1.48m	1.39m	1.855m	2.48m	2.48m
G-Overall Width	0.76m	0.81m	0.79m	0.84m	1.19m
H-Wheelbase	1.05m	1.11m	1.36m	1.89m	1.89m
I-Ground clearance (Stowed)	0.06m	0.85m	0.083m	0.1m	0.1m
J-Ground Clearance (Raised)	0.02m	0.02m	0.016m	0.02m	0.02m
Performance					
Capacity of Extension	100kg	100kg	113kg	113kg	113kg
Platform Capacity	240kg	230kg	230kg	230kg	450kg
Max. Number of Workers	2	3	3	5	7
Driving Speed (Stowed)	4.0km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Driving Speed (Raised)	0.5km/h	0.5km/h	0.8km/h	0.8km/h	0.8km/h
Turning radius (outside)	1.35m	1.35m	1.64m	3.1m	2.2m
Turning radius (inside)	0.3m	0.3m	0.3m	0.3m	0.3m
Lifting speed	4-6m/min	4-6m/min	3-5m/min	3-5m/min	3-5m/min
Gradeability	0.25	0.25	0.25	0.25	0.25
Max. Working Angle	2°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°
Tire(drive wheel)	Φ230×80mm	Φ255×80mm	Φ305×100mm	Φ381×127mm	Φ381×127mm
Power					
Battery	2×12V/80ah	2×12V/103ah	4×12V/80ah	4×6V/200ah	4×6V/200ah
Charger	24V/15A	24V/15A	24V/30A	24V/30A	24V/30A
Weight					
Gross	890kg	1010kg	1620kg	1880kg	2150kg

