

KINGLIFT

SCISSOR LIFTS SERIES



HIGHLIGHTS

High Performance

- ▶ The pedal extension platform can be quickly rolled out to the operating point
- ▶ The swivel chassis allows for easy maintenance
- ▶ Convenient for working in tight spaces
- ▶ 25% climbing ability, able to smoothly climb up the slope
- ▶ The foldable fence reduces the volume of the whole machine
- ▶ Fault codes are automatically displayed for easy maintenance

FEATURES

Safety Configuration

- Automatic braking system
- Emergency descent system
- Charging protection system
- Oil pipe explosion-proof system
- Tilt protection system
- Automatic pothole protection
- Emergency stop button
- Tamper-proof
- Platform self-locking door
- Safe maintenance support rod
- Fault diagnosis system
- Foldable fence

Other Configuration

- Full Self-propelled
- Non-marking tire
- 4×2 drive
- Extended platform
- Horn& Buzzer
- Standard transport forklift hole
- Work schedule
- Continuously variable speed
- Remote car lock
- GPS positioning



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT SCISSOR LIFT

Model	GTJZ0808HD	GTJZ0812HD	GTJZ1012HD	GTJZ1212HD	GTJZ1414HD
Size					
Working Height	9.80m	9.80m	11.80m	13.80m	15.8m
A-Platform Height-Elevated	7.80m	7.80m	9.80m	11.80m	13.80m
B-Platform Height-Stowed	1.2m	1.2m	1.35m	1.48m	1.495m
C-Platform Length	2.26	2.29	2.29	2.29	2.64
D-Platform Width	0.84	1.12	1.12	1.12	1.13
Platform Extension	0.9m	0.9m	0.9m	0.9m	0.9m
E-Overall Height (unfolded guardrail)	2.32m	2.32m	2.46m	2.58m	2.595m
Overall height (folded guardrail)	1.85m	1.82m	1.92m	2.05m	2.060m
F-Overall Length	2.48	2.48	2.48	2.48	2.84
G-Overall Width	0.84	1.19	1.19	1.19	1.4m
H-Wheelbase	1.89m	1.89m	1.89m	1.89m	1.895m
I-Ground Clearance (Stowed)	0.1	0.1	0.1	0.1	0.1
J-Ground Clearance (Raised)	0.02	0.02	0.02m	0.02m	0.02m
Performance					
Capacity of Extension	113kg	113kg	113kg	113kg	113kg
Platform Capacity	230kg	450kg	320kg	320kg	227kg
Max. Number of Workers	1 person+70kg	3 Person	2 Person	2 Person	1 person+70kg
Driving Speed (Stowed)	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Driving Speed (Raised)	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Turning Radius (Outside)	3.1m	2.2m	2.2m	2.2m	2.2m
Turning Radius (Inside)	0m	0m	0m	0m	0m
Lifting Speed	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min
Gradeability	0.25	0.25	0.25	0.25	0.25
Max. Working Angle	1.5°/3°	2°/3°	1.5°/3°	1.5°/3°	1.5°/3°
Tire(Drive Wheel)	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm
Power					
Battery	4×12V/240ah	4×6V/240ah	4×6V/240ah	4×6V/240ah	4×12V/240ah
Charger	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A
Weight					
Gross	2030kg	2280kg	2540kg	2880kg	3400kg

