



VEHICLE MOUNTED SCISSOR LIFT





HIGHLIGHTS

High Performance

- ▶ Wide working table
- ▶ High bearing capacity
- ▶ Multiple people can work at the same time
- ▶ Adopt high-strength manganese steel structure
- ▶ It is applicable to site, plant, station, airport, lifting equipment maintenance, field power facilities maintenance, steel frame structure plant maintenance, etc.



FEATURES

Detailed

- Hydraulic hose: 2 - 10 - 43MPa double - layer steel mesh pipe
- Guide rail: 5mm flat plate is bent to make the guide rail
- Outtrigger: 100x50x3.75mm rectangular tube matching
- Spraying treatment: use electrostatic powder spraying
- Hydraulic oil: 46# Great Wall anti-wear hydraulic oil
- Lifting speed: 4-6 m/min, adjustable falling speed
- Scissor rod: 120x60x3.75mm rectangular tube
- Rust removal: shot blasting, sand blasting
- Chassis: 100x50x3.75mm rectangular tube
- Shaft pin: 45# round steel, galvanized
- Control form: up and down control
- Pumping station: Anshan Lisheng
- Oil cylinder: HSG80/50 1-4 pieces
- Table: 3mm flat plate bending
- Tires: 3 pieces pneumatic tires
- Power and voltage: DC48V
- Distribution box: Delixi



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT VEHICLE MOUNTED SCISSOR LIFT

Model(tricycle)	QYCZ0.5-6	QYCZ0.5-8	QYCZ0.5-10	QYCZ0.3-11
Size				
Working Height	8m	10m	12m	13m
A-Platform Height-Elevated	6m	8m	10m	11m
B-Platform Height-Stowed	1.5m	1.6m	1.7m	1.8m
C-Platform Length	2.1m	2.1m	2.1m	2.1m
D-Platform Width	0.83m	0.83m	1.23m	1.23m
E-Overall Height	2.6m	2.7m	2.8m	2.9m
F-Overall Length	4m	4m	4m	4m
G-Overall Width	1.35m	1.35m	1.35m	1.35m
Performance				
Extension Platfrom Aavailable	×	×	×	×
Platform Capacity	500kg	500kg	500kg	300kg
Max. Number of Workers	6	6	6	4
Lifting Speed	4-6m/min	4-6m/min	4-6m/min	4-6m/min
Descending speed	Adjustable	Adjustable	Adjustable	Adjustable
Power				
Battery	Same vehicle use	Same vehicle use	Same vehicle use	Same vehicle use
Weight				
Gross	1280kg	1500kg	1700kg	1800kg

