

# KINGLIFT

## TELESCOPIC BOOM LIFTS

### ELECTRIC SERIES



#### HIGHLIGHTS

##### High Performance

- ▶ It has large horizontal ductility, wide operation range and high efficiency.
- ▶ Simple operation, good stability, no impact and no shaking.
- ▶ Intelligent visualization, high-brightness large screen.
- ▶ Adopts imported engines to provide strong power for the equipment.
- ▶ The unique four-wheel drive traction system delivers strong traction for it.
- ▶ Max. climbing ability up to 45%.

#### FEATURES

##### Safety Configuration

- |   |                                  |
|---|----------------------------------|
| Automatic leveling of working platform    | 360° rotation of platform        |
| Emergency descent system                  | Emergency safety pump            |
| Fault diagnosis system                    | Self-locking platform door       |
| Emergency braking system                  | Centralized electric control box |
| Proportional control                      |                                  |
| Turntable safetylock pin                  |                                  |
| Dual cylinder same-liquid steering system |                                  |
| Chassis floating leveling device          |                                  |

##### Other Configuration

- Hydraulic rotary working platform
- Trumpet
- Solid tire
- Timer
- Imported overweight sensor
- 40Cr steering link
- Swing-out engine bracket
- Wide chassis form chassis
- Footswitch
- 160° rotation of working basket
- Three handle lever



[www.kingliftcn.com](http://www.kingliftcn.com)

CE | ENEC | TUV | ISO | CCC | IPAF

## DETAILED PARAMETERS OF KINGLIFT TELESCOPIC BOOM LIFTS

### ELECTRIC SERIES

Model	QYZB-22D	QYBZ-26D
Size		
Working Height	23.80m	27.8m
A-Platform Height-Elevated	21.8m	25.8m
B-Platform Length	2.44m	2.44m
C-Platform Width	0.91m	0.91m
D-Overall Height	2.7m	2.9m
E-Overall Length	10.80m	12.50m
F-Overall Width	2.49m	2.49m
G-Wheelbase	2.5	3m
H-Ground Clearance-middle	0.45m	0.43m
Performance		
Platform Capacity	250kg	300/460KG
Max. Number of Workers	2	2
Max working radius	15.8m	16/18.0m
Driving Speed (Stowed)	5.2km/h	5.2km/h
Driving Speed (Raised)	1.1km/h	1.1km/h
Turning Radius (Outside)	5.6m	5.98m
Turning Radius (Inside)	2.4m	2.5m
Turntable tail scanning	1.4m	1.48m
Platform leveling	Auto	Auto
Platform rotation	160°	160°
Turntable rotation angle	Continuous 360 °	Continuous 360 °
Gradeability	45%	45%
Max Working Angle	5°	5°
Tire(Drive Wheel)	36*14-20	385/65--24
Power		
Drive steering	4 *4*2	4 *4*2
Weight		
Gross	11800kg	11800kg

