

KINGLIFT

ARTICULATING BOOM LIFTS

CRAWLER SERIES



HIGHLIGHTS

High Performance

- Obstacles can be overcome, fast erection, automatic hydraulic support feet;
- Flexible boom, more practical for complex and narrow working space.
- Multi-point operation without moving;
- Provides up, down and across multi-directional positioning functions;
- The height of each foot can be adjusted according to the terrain to achieve a level state of the platform;

FEATURES

Safety Configuration

Automatic hydraulic support legs
Controller below the platform
Automatic leveling device
Outrigger Controller
Emergency descent system
Equipment operation device

Other Configuration

Can overcome obstacles
Upper control handle
360° rotation of platform
Track tires
Spirit level



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT

ARTICULATING BOOM LIFTS CRAWLER SERIES

Model	GTZZ14	GTZZ16
Size		
Working Height	16m	18m
A-Platform Height-Elevated	14m	16m
B-Platform Length	1.1m	1.1m
C-Platform Width	0.8m	0.8m
D-Overall Height	2.2m	2.2m
E-Overall Length	6.06m	7m
F-Overall Width	1.935m	1.73m
G-Wheelbase	x	x
Leg span (longitudinal)	3.892m	3.892m
Leg span (horizontal)	4.198m	4.198m
Performance		
Max working distance	8.5m	9.5m
Platform Capacity	200kg	200kg
Max. Number of Workers	1	1
Driving Speed (Stowed)	1.8km/h	1.8km/h
Driving Speed (Raised)	0km/h	0km/h
Turning Radius	0	0
Turntable rotation angle	360°	360°
Gradeability	0.3	0.3
Max. Working Angle	1.5°/3°	1.5°/3°
Tire(Drive Wheel)	Φ381×127mm	Φ381×127mm
Power		
Battery	8×12V/100ah	8×12V/100ah
Charger	48V/35A	48V/35A
Weight		
Gross	3900kg	4400kg

