KINGLIFT



ALUMINUM ALLOY LIFTS

SINGLE MAST SERIES

HIGHLIGHTS

High Performance

- ▶ High-strength high-quality aluminum alloy material.
- ▶ Beautiful appearance, small size and light weight, one person can drag and walk.
- The platform itself wears safety steel ropes and safety protection devices.
- The equipment is equipped with a remote control box, and the lifting can be controlled by the remote control.
- The equipment adopts polyurethane tires, which has low walking resistance, low sound and does not hurt the ground.
- According to the number of masts, the products are divided into single mast, double masts, three masts and four masts.

FEATURES

Standard Configuration

Guardrail

Door Quick Lock Device

Remote Controller

Emergency Descent valve

Polyurethane Tire

Spirit Level

Invisible Outriggers

Accessories & Options

battery lift AC+DC lift **Explosion-proof Electrical Appliances** Assisted Walking Hand Pump



www.kingliftcn.com



ALUMINUM ALLOY LIFTS SINGLE MAST SERIES

Model	QYLH4-100-1	QYLH6-100-1	QYLH4-150-1	QYLH6-150-1	QYLH8-130-1	QYLH10-130-1
Size						
Working Height	6m	8m	6m	8m	10m	12m
A-Platform Height-Elevated	4m	6m	4m	6m	8m	10m
B-Platform Length	0.64m	0.65m	0.65m	0.65m	0.65m	0.65m
C-Platform Width	0.5m	0.5m	0.65m	0.65m	0.65m	0.65m
D-Overall Height	1.7m	1.7m	1.97m	1.97m	1.97m	1.97m
E-Overall Length	1.45m	1.45m	1.42m	1.42m	1.42m	1.42m
F-Overall Width	0.6m	0.6m	0.78m	0.78m	0.78m	0.78m
G-Wheelbase	1.29m	1.29m	1.29m	1.29m	1.29m	1.29m
H-Ground Clearance	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m
Performance						
Platform Capacity	100kg	100kg	150kg	150kg	130kg	130kg
Max. Number of Workers	1	1	1	1	1	1
Leg deployment length	1.91m	1.91m	1.91m	1.91m	1.91m	1.91m
Leg deployment width	1.7m	1.7m	1.7m	1.7m	1.7m	1.7m
Lifting Speed	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min
Tire(Drive Wheel)	6in	6in	6in	6in	6in	6in
Power						
Battery	Optional	Optional	Optional	Optional	Optional	Optional
Weight						
Gross	280kg	360kg	340kg	360kg	380kg	420kg







