

KINGLIFT

ALUMINUM ALLOY LIFTS

DOUBLE/TRIPLE MASTS SERIES



HIGHLIGHTS

High Performance

- ▶ High-strength high-quality aluminum alloy material.
- ▶ Beautiful appearance, small size and light weight, one person can drag and walk.
- ▶ The platform itself wears safety steel ropes and safety protection devices.
- ▶ The equipment is equipped with a remote control box, and the lifting can be controlled by the remote control.
- ▶ The equipment adopts polyurethane tires, which has low walking resistance, low sound and does not hurt the ground.
- ▶ According to the number of masts, the products are divided into double mast, three mast and four mast.

FEATURES

Standard Configuration

- Guardrail
- Door Quick Lock Device
- Remote Controller
- Emergency Descent valve
- Polyurethane Tire
- Spirit Level
- Invisible Outriggers

Accessories & Options

- battery lift
- AC+DC lift
- Explosion-proof Electrical Appliances
- Assisted Walking
- Hand Pump



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT

ALUMINUM ALLOY LIFTS

DOUBLE/TRIPLE MASTS SERIES

Model	QYLH6-300-2	QYLH8-300-2	QYLH10-250-2	QYLH12-200-2	QYLH14-150-2	QYLH16-200-2	QYLH18-200-2	QYLH20-200-2
Size								
Working Height	8m	10m	12m	14m	16m	14m	16m	18m
A-Platform Height-Elevated	6m	8m	10m	12m	14m	12m	14m	16m
B-Platform Length	1.2m	1.2m	1.5m	1.5m	1.5m	1.5m	1.5m	1.5m
C-Platform Width	0.63m	0.63m	0.63m	0.63m	0.63m	0.9m	0.9m	0.9m
D-Overall Height	2m	2m	2m	2m	2.35m	1.9m	2.35m	2.65m
E-Overall Length	1.55m	1.55m	1.84m	1.84m	1.95m	1.85m	1.85m	1.85m
F-Overall Width	0.85m	0.85m	0.85m	0.85m	1.05m	1.1m	1.1m	1.15m
G-Wheelbase	1.23m	1.23m	1.23m	1.23m	1.23m	1.23m	1.23m	1.23m
H-Ground Clearance	0.06m	0.06m	0.06m	0.06m	0.06m	0.06m	0.06m	0.06m
Performance								
Platform Capacity	300kg	300kg	250kg	200kg	150kg	200kg	200kg	200kg
Max. Number of Workers	2	2	2	2	2	2	2	2
Leg deployment length	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m
Leg deployment width	1.69m	1.69m	1.69m	1.69m	1.69m	1.69m	1.69m	1.69m
Lifting Speed	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min
Tire	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in
Power								
Battery	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weight								
Gross	510kg	550kg	690kg	730kg	790kg	1050kg	1120kg	1200kg

