

KINGLIFT

ALUMINUM ALLOY LIFTS

ASSISTED WALKING SERIES



HIGHLIGHTS

High Performance

- ▶ High-strength high-quality aluminum alloy material.
- ▶ Beautiful appearance, small size and light weight.
- ▶ Battery-assisted walking One person can easily move to the work site
- ▶ The platform itself wears safety steel ropes and safety protection devices.
- ▶ The equipment is equipped with a remote control box and the lifting can be controlled by the remote controller.
- ▶ According to the number of masts, the products are divided into single mast, double mast, three mast and four mast.

FEATURES

Standard Configuration

- Guardrail
- Door Quick Lock Device
- Remote Controller
- Emergency Descent valve
- Polyurethane Tire
- Spirit Level
- Invisible Outriggers
- Lifting and down by Battery
- Assisted Walking

Accessories & Options

- AC+DC lift
- Explosion-proof Electrical Appliances
- Hand Pump



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT

ALUMINUM ALLOY LIFTS

ASSISTED WALKING SERIES

Model	QYLH4-100-1	QYLH6-100-1	QYLH8-100-1	QYLH10-100-1	QYLH6-200-2	QYLH8-200-2	QYLH10-200-2	QYLH12-200-2	QYLH14-200-2
Size									
Working Height	6m	8m	10m	12m	8m	10m	12m	14m	16m
A-Platform Height-Elevated	4m	6m	8m	10m	6m	8m	10m	12m	14m
B-Platform Length	0.65m	0.65m	0.65m	0.65m	1.2m	1.2m	1.5m	1.5m	1.5m
C-Platform Width	0.5m	0.5m	0.65m	0.65m	0.63m	0.63m	0.63m	0.63m	0.63m
D-Overall Height	1.98m	1.98m	1.98m	1.98m	1.88m	1.88m	1.98m	1.98m	2.34m
E-Overall Length	1.73m	1.71m	1.85m	1.85m	1.85m	1.85m	2.15m	2.15m	2.25m
F-Overall Width	0.78m	0.78m	0.78m	0.78m	0.85m	0.85m	0.85m	0.85m	1.05m
G-Wheelbase	1.2m	1.2m	1.2m	1.2m	1.2m	1.2m	1.2m	1.2m	1.2m
H-Ground Clearance	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m	0.05m
Performance									
Platform Capacity	100kg	150kg	130kg	130kg	300kg	300kg	250kg	200kg	150kg
Max. Number of Workers	2	2	2	2	2	2	2	2	2
Leg deployment length	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m	1.81m
Leg deployment width	1.7m	1.7m	1.7m	1.7m	1.7m	1.7m	1.7m	1.7m	1.7m
Lifting Speed	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min	3-5m/min
Tire	6in	6in	6in	6in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in	Front 8 in rear 7 in
Power									
Battery	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weight									
Gross	480kg	460kg	520kg	550kg	710kg	78kg	860kg	970kg	1020kg
Product advantages	High-strength high-quality aluminum alloy material, Q235 steel plate thickened chassis, prevent bumps, can be used with forklifts, convenient and fast transportation, the equipment is equipped with lower control and remote control to facilitate the operation of aerial working, saving time and efficiency								
Applicable place	It is suitable for factories, hotels, restaurants, stations, airports, theaters, exhibition halls and other places. It can pass through the general lobby and elevators. It is very convenient to use. It is the best safety for maintenance of machinery, paint decoration, replacement of lamps and appliances, cleaning and maintenance, etc. companion.								

