KINGLIFT



ALUMINUM ALLOY LIFTS

SELF-PROPELLED SERIES

HIGHLIGHTS

High Performance

- ▶ High-strength high-quality aluminum alloy material.
- ▶ Beautiful appearance, small size and light weight.
- ▶ The platform itself wears safety steel ropes and safety protection devices.
- ▶ One person can control the walking and lifting through the handle.
- ► The equipment adopts polyurethane tires, which has low walking resistance, low sound and does not hurt the ground.
- ▶ Products are divided into single mast and double mast according to the number of masts.

FEATURES

Standard Configuration

Emergency descent valve Non-marking tires

Spirit level

PCU handle

Lower control system

Battery lift



www.kingliftcn.com



DETAILED PARAMETERS OF KINGLIFT ALUMINUM ALLOY LIFTS SELF-PROPELLED SERIES

Model	QYLH06-1	QYLH08-1	QYLH04-2	QYLH06-2	QYLH08-2
Size					
Working Height	8m	10m	6m	8m	10m
A-Platform Height-Elevated	6m	8m	4m	6m	8m
B-Platform Length	0.65m	0.65m	0.65m	0.65m	0.65m
C-Platform Width	0.5m	0.5m	0.9m	0.9m	0.9m
D-Overall Height	2.11m	2.11m	1.993m	1.993m	1.993m
E-Overall Length	1.45m	1.65m	1.336m	1.336m	1.336m
F-Overall Width	0.768m	0.768m	0.91m	0.91m	0.91m
Performance					
Platform Capacity	150kg	150kg	150kg	150kg	150kg
Max. Number of Workers	1	1	1	1	1
Lifting Speed	3-5 m/min	3-5 m/min	3-5 m/min	3-5 m/min	3-5 m/min
Weight					
Gross	830kg	880kg	980kg	1100kg	1136kg
Product advantages	High-strength high-quality aluminum alloy material, Q235 steel plate thickened chassis, prevent bumps, can be used with forklifts, convenient and fast transportation, the equipment is equipped with lower control and remote control to f acilitate the operation of aerial working, saving time and efficiency				
Applicable place	It is suitable for factories, hotels, restaurants, stations, airports, theaters, exhibition halls and other places. It can pass through the general lobby and elevators. It is very convenient to use. It is the best safety for maintenance of machiner y, paint decoration, replacement of lamps and appliances, cleaning and maintenance,				

etc. companion





