







# **TAILED PARAMETERS OF KINGLIFT**

Model	QYDCQ-6	QYDCQ-8	QYDCQ-10	QYDCQ-12			
Size							
A-Overall Length	11m						
B-Overall Width	2m						
C-Overall Height	1.1m						
D-Slope Length	7.15m						
E-Slope Width	2m						
Performance							
Loading Capacity	6T	8T	10T	12T			
Lifting range	1.1-1.7m						
Weight							
Gross	2250kg	2350kg	2450kg	3000kg			

# **YARD RAMP**

Model	QYDCQ-6	QYDCQ-8	QYDCQ-10	QYDCQ-12			
Size							
A-Overall Length		11m					
B-Overall Width		2m					
C-Overall Height		1.1m					
D-Slope Length		7.15m					
E-Slope Width		2m					
	ļ.	Performance					
Loading Capacity	6T	8T	10T	12T			
Lifting range		1.1-1.7m					
		Weight					
Gross	2250ka	2350kg	2450ka	3000ka			

## HIGHLIGHTS

#### **High Performance**

- ► Manual/electric lifting operation can be realized
- ► Reinforced steel, durable and safer
- The slope is longer and the cover is slower
- ▶ Bridge deck anti-skid treatment, safe and reliable

### Safety Configuration

**FEATURES** 

Strengthen the connecting chain Non-slip mesh diamond mesh Triangle brake pad Multifunctional auxiliary legs

#### Other Configuration

Foldable tailgate Solid tire Hydraulic cylinder Hand hydraulic pump

#### **Accessories & Options**

battery lift AC lift



