

# KINGLIFT TELESCOPIC LIFTS



## HIGHLIGHTS

### High Performance

- ▶ Beautiful appearance, small size and light weight
- ▶ The platform itself wears safety steel ropes and safety protection devices
- ▶ One person can control the walking and lifting through the handle
- ▶ The equipment adopts polyurethane tires, which has low walking resistance, low sound and does not hurt the ground.

## FEATURES

### Standard Configuration

- EmergencyDescent valve
- Non-marking tires
- Spirit level
- PCU handle
- Lower control system
- Battery lift



[www.kingliftcn.com](http://www.kingliftcn.com)

CE | ENEC | TUV | ISO | CCC | IPAF

## DETAILED PARAMETERS OF KINGLIFT TELESCOPIC LIFTS

Model	M8+	M12+
Size		
Working Height	6.58m	7.66m
A-Platform Height-Elevated	4.58m	5.66m
B-Platform Length	1.035m	1.035m
C-Platform Width	0.76m	0.76m
D-Overall Height	1.9m	1.9m
E-Overall Length	1.38m	1.38m
F-Overall Width	0.76m	0.76m
G-Ground Clearance	0.06m	0.06m
Performance		
Platform Capacity	230kg	230kg
Max. Number of Workers	1	1
Driving Speed (Stowed)	4Km/h	4Km/h
Driving Speed (Raised)	0.8Km/h	0.8Km/h
Lifting Speed	12s	12s
Gradeability	0.25	0.25
Weight		
Gross	700kg	800kg

