

KINGLIFT HOME LIFT



HIGHLIGHTS

High Performance

- ▶ There is no need to set up a high-demand and high-cost machine room above the hoistway, and it can be flush with the roof.
- ▶ Small footprint: The hydraulic transmission system relies on oil pipes to transmit power without a machine room and without a bottom pit, and the minimum installation space is only 700X800mm.
- ▶ High well utilization rate: the hydraulic elevator does not need to be equipped with a counterweight device, which can improve the utilization rate of the well area.
- ▶ Low structural strength requirements for the hoistway: The vertical compliance of the hydraulic elevator car's self-weight and load all act on the foundation of the hoistway through the hydraulic cylinder, and the requirements for the building performance of the wall and top of the hoistway are low.

FEATURES

Safety Configuration

- Active thermal protection
- Safety loop segment detection
- Car position switch
- Car emergency stop switch
- Safety gear safety contacts
- Speed limiter safety contact
- Do not open the door switch

Other Configuration

- Stroke limit
- Control box
- Floor calling box
- Link alignment pin
- Base bracket
- Top bracket
- Elevator car light curtain
- Main power switch box
- Hydraulic pump station

Accessories & Options

- Power failure emergency leveling ARD
- Emergency phone
- Automatically send rescue information function
- Background music/Voice announcement
- Disabled Access Function
- Through door
- Optional opening type of the door
- Emergency power supply function



www.kingliftcn.com

CE | ENEC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT HOME LIFT

QIYUN GROUP PROFESSIONAL CUSTOMIZATION		
Perfect engineer team, Qiyun Group's own production base, Can be specially customized according to your needs, fast design, fast production		
Perfect Engineer Team	Seven Production Bases	Style Customization
Load Customization	Size Customization	Height Customization

①

The building has a dedicated elevator shaft

②

There is suitable space in the middle of the winding staircase

③

Have a hollow hall or room

④

If there is suitable space in the building, the home lifting platform can only be installed indoors

⑤

No suitable space in the building

⑥

Where permitted, install household lifting platforms in indoor technology wells

⑦

Drill a suitable hole in the floor and install a hoistway to install a household lifting platform

In 12345 occasions, a shaft for small villa elevators needs to be installed.

Customers can use metal frames or concrete to build shafts in advance.

We recommend customers to choose the special frame shaft for villa elevators

