

PARAMETER

| Size | 100mm(L)*53mm(W)*17mm(H) | Weight | 81g |
|---------------------|--------------------------|------------------|--------|
| Working Temperature | -30°C to 80°C | Built-in Battery | 180mAh |
| Working Voltage | 9-75V | | |

HARDWARE SPECIFICATION

| Location Accuracy | <=10m | Channel | 20 Class |
|-------------------|--|----------------------|----------|
| GPS Chip | AT6558D | GPS Sensitivity | -160dBm |
| Frequency | 850/900/1800/1900MHZ, B1/B2/B5/B8 UMTS | Tracking Sensitivity | -162dBm |
| | Hot Start<1SEC(Open Sky) | Power LED Indicator | Red |
| Positioning Time | Warm Start<15SEC | GPS LED Indicator | Blue |
| | Cold Start<32SEC(Open Sky) | GPRS LED Indicator | Yellow |
| GSM Antenna | FPC Antenna | | |
| GPS Antenna | Built-in Ceramic Antenna | | |

Class12. TCP/IP Built-in GSM Module

SOFTWARE SPECIFICATION

RS232

| OTA Upgrade | Support | ACC Detection | Support |
|--------------------------|----------------------------------|-----------------|---------|
| Function Port Definition | Support | Geo-fence | Support |
| Parameter Setting | SMS Command, Platform | Cut-wire Alarm | Support |
| GPRS Upload | Upload Interval Every 10 Seconds | Vibration Alarm | Support |
| Third-party Checking | WEB/APP | | |

FUNCTION



Real-time Tracking



Remotely Cut-off Petrol/Electricity



SOS Emergency Call



Remotely Voice Monitoring



Built-in Battery



Multiple Function Ports

APPLICATION



Car Tracking



Fleet Management



Truck Tracking