

PARAMETER

Size	77mm(L)*41mm(W)*27mm(H)
Working Temperature	-25°C to 75°C
Working Current	60-80mA

Weight Built-in Battery

4200mAh

HARDWARE SPECIFICATION

Location Accuracy	<=10m	Channel	20 Class
GPS Chip	MTK	GPS Sensitivity	-144dBm
GSM Frequency	850/900/1800/1900MHZ	Tracking Sensitivity	-160dBm
	Hot Start<2SEC(Open Sky)	GPRS LED Indicator	Red
Positioning Time	Warm Start<15SEC	GPS LED Indicator	Blue
	Cold Start<38SEC(Open Sky)	Light-sensor	Support
GSM Antenna	Spring Antenna		
GPS Antenna	Built-in Ceramic Antenna		

Class12. TCP/IP Built-in GSM Module

SOFTWARE SPECIFICATION

Data Upgrade Port	Not Support	ACC Detection	Not Support
Function Port Definition	Not Support	Geo-fence	Support
Parameter Setting	SMS Command, Platform	Low Battery Alarm	Support
GPRS Upload	Upload Interval Every 10 Seconds	Vibration Alarm	Not Support
Third-party Checking	WEB/APP	Disassemble Alarm	Support

FUNCTION



Real-time Tracking



Light Sensor and Disassemble Alarm



Strong Magnetic



User Define Geo-fence



Long Life Battery



Trace Playback

APPLICATION



Container Tracking



Trailer Tracking



Luggage Tracking