




DCAEX

# DIE-CAST ALUMINUM EXIT SIGN

## DIMENSIONS



## ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

## ELECTRICAL

- 120-347V.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V long life maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Internal toggle switch for red or green letter color selection for RG models

## MOUNTING

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

## HOUSING

- Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

## OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

## WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA,
- UL Listed for damp locations (0°C-50°C).
- Certified to CEC under Title 20 Regulations.

## ORDERING INFORMATION

Special voltage options available. Check with your Best Lighting Representative.

<sup>1</sup> Available only with EM units.

<sup>2</sup> Available only with AC units.

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	FACE PANEL	BATTERY	OPTIONS
DCAEX	1	Single Face	R Red	W White	W White	(blank) AC-Only SDT Self-Diagnostics <sup>1</sup>
	2	Double Face	G Green	B Black	B Black	EM Battery Backup 2C Dual Circuit Operation <sup>2</sup>
	3	Universal Single/Double Face	RG Red/Green	A Aluminum	A Aluminum	TP Tamper-Proof
						USA Assembled In USA